

Appl. No.: 10/023,284  
Amdt. dated: 10/7/2005

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims**

What is claimed is:

1. (Cancelled).
2. (Previously Presented). The pump-motor assembly of claim 3, wherein the motor unit includes an end bell and a lead housing.
3. (Currently Amended). A pump-motor assembly, comprising:  
a motor unit including an end bell and a lead housing;  
a pump assembly having components, said pump assembly having a predetermined cross-sectional area; and  
a shell having an expanded portion that is relatively larger than said predetermined cross-sectional area, wherein the shell encloses the pump assembly components and the motor unit, and the expanded portion ~~defines~~ defining a cavity between said shell and said ~~housing~~ motor unit, wherein the shell aligns the pump assembly components to the motor unit, and wherein the shell contacts the end bell.
4. (Previously Presented). The pump-motor assembly of claim 3, wherein the shell contacts the lead housing.
5. (Previously Presented). The pump-motor assembly of claim 3, wherein the shell contacts the end bell and the lead housing.
6. (Cancelled)

Appl. No.: 10/023,284  
Amdt. dated: 10/7/2005

7. (Previously Presented). The pump-motor assembly of claim 3, wherein the inner diameter of the expanded portion of the shell is at least four inches.

8. (Cancelled).

9. (Previously Presented). The pump-manifold assembly of claim 11, wherein the motor unit includes an end bell and a lead housing.

10. (Original). The pump-manifold assembly of claim 9, wherein the shell contacts the end bell.

11. (Currently Amended). A pump-manifold assembly, comprising:

a manifold;

a pump-motor assembly; and

a piping assembly connecting the pump-motor assembly to the manifold, wherein the pump-motor assembly comprises:

a motor unit including an end bell and a lead housing;

a pump assembly having components, said pump assembly having a predetermined diameter; and

a shell having an expanded portion relative to said pump assembly, wherein the shell encloses the pump assembly components and the motor unit and a cavity is defined in the expanded portion between said motor housing unit and said shell, wherein the shell aligns the pump assembly components to the motor unit, and wherein the shell contacts the lead housing.

12. (Cancelled).

13. (Cancelled).

Appl. No.: 10/023,284  
Amdt. dated: 10/7/2005

14. (Previously Presented). The pump-manifold assembly of claim 11, wherein the inner diameter of the expanded portion of the shell is at least four inches.

15. (Currently Amended). A petroleum distribution system for use in a petroleum dispensing station, comprising:

a petroleum storage tank;

a petroleum dispenser;

a pump-manifold assembly, in fluid communication with the petroleum dispenser, having a pump-motor assembly, wherein the pump-motor assembly is disposed in the storage tank and the pump-motor assembly comprises:

a motor unit having an end bell and a lead housing;

a pump assembly having components and having a predetermined diameter; and

a shell having an expanded portion relative to said predetermined diameter, wherein the shell encloses the pump assembly components and the motor unit and the expanded portion defines a fluid cavity between the motor unit and the ~~pump assembly~~ shell and wherein the shell aligns the pump assembly components to the motor unit, wherein the shell contacts the end bell and the lead housing.

16. (Cancelled).

17. (Cancelled).

18. (Cancelled)

19. (Cancelled).

20. (Cancelled).

21. (Original). The petroleum distribution system of claim 15, wherein the inner diameter of the expanded portion of the shell is at least four inches.

22. (Previously Presented). A method for increasing fluid dispensing flow rate in a petroleum distribution system for use in a petroleum dispensing station, comprising:

providing a petroleum distribution system including a petroleum storage tank; a petroleum dispenser; a pump-manifold assembly, in fluid communication with the petroleum

Appl. No.: 10/023,284  
Amdt. dated: 10/7/2005

dispenser, having a pump-motor assembly, wherein the pump-motor assembly is disposed in the storage tank and the pump-motor assembly includes a motor unit which includes an end bell and a lead housing, a pump assembly having components and having a predetermined diameter, and a shell having an expanded portion relative to said predetermined diameter, wherein the shell encloses the pump assembly components and the motor unit and the expanded portion defines a fluid cavity between the motor unit and the shell and wherein the shell aligns the pump assembly components to the motor unit, said shell and said motor unit configured so that said shell contacts said end bell and said lead housing; and

energizing the pump-motor assembly to pressurize the petroleum distribution system.

23. (Previously Presented). A method for increasing dispensing capacity in a petroleum distribution system for use in a petroleum dispensing station where the maximum dispensing flow rate is capped, comprising:

providing a capped maximum dispensing flow rate;

providing a petroleum distribution system including a petroleum storage tank; a petroleum dispenser; a pump-manifold assembly having a predetermined diameter, in fluid communication with the petroleum dispenser, having a pump-motor assembly, wherein the pump-motor assembly is disposed in the storage tank and the pump-motor assembly includes a motor unit having an end bell and a lead housing, a pump assembly having components, and a shell having an expanded portion relatively larger than said predetermined diameter, wherein the shell encloses the pump assembly components and the sealed motor unit with the expanded portion disposed around the motor unit, wherein the shell aligns the pump assembly components to the motor unit, said shell and said motor unit configured so that said shell contacts said end bell and said lead housing; and

energizing the pump-motor assembly to pressurize the petroleum distribution system.

24. (Original). The method of claim 23, wherein the provided capped maximum dispensing flow rate is ten gallons per minute.